

SoluJET® 2707B

Solvent ink for non-porous media



TECHNICAL DATA SHEET

SoluJET® 2707B which a methanol free blue solvent TIJ 2.5 ink is designed for track and trace coding and marking and other high-productivity industrial packaging printing applications. SoluJET® 2707B ink provides long decap time, good adhesion and rub resistance, excellent sharpness and barcode readability on semi-porous and non-porous substrates such as lacquered aluminum foils and packaging films.

Technical Specifications

SoluJET® 2707B Print Cartridge	
Ink type	Blue dye solvent ink
Print cartridge type	HP 45si
Resolution	Up to 600 dpi, recommended 300 x 300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	9.0 V
Fire pulse width	2.2 µs
Pulse warming	OFF
Decap time	Up to 1 h
Drying time	5 - 7 s at 300 x 300 dpi
Throw distance	Up to 5 mm
Average delivered ink	36 mL (vertical) and 34 mL (horizontal)
Average drop volume	41 pL
Operating conditions	10 °C to 35 °C, 35% to 90% RH
Shipping / storage temperature	5 °C to 30 °C
Best before	12 months from filling date

Cartridge Shipping & Storage

- The cartridge should be stored in vacuum sealed pouch until used.
- Use the cartridge within two weeks of removing it from vacuum sealed pouch for best performance.
- Store the cartridge with a clip placed over the printhead. Horizontal position is recommend.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with ethanol (> 98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

Ordering Information

Product number	Product description
2707B42A	SoluJET® 2707B Print Cartridge

